

Bearing No.	Dimensions (mm)													Load Ratings			Limiting Speed nG rpm
	d	D	B	b	d1	d2	D1	l	J	r ₁ mim	r mim	t	m ⁽¹⁾	Ca (KN)	Coa (KN)	Cua (KN)	
ZKLF 1255.2RS	12	55	25	3	25	6.5	33.5	17	42	0.6	0.3	120	0.37	17	24.7	0.91	3800
ZKLF 1260.2RS	15	60	25	3	28	6.5	36	17	46	0.6	0.3	120	0.43	17.9	28	1.04	3500
ZKLF 1762.2RS	17	62	25	3	30	6.5	38	17	48	0.6	0.3	120	0.45	18.8	31	1.15	3300
ZKLF 2068.2RS	20	68	28	3	34.5	6.5	44	19	53	0.6	0.3	90	0.61	26	47	1.74	3000
ZKLF 2575.2RS	25	75	28	3	40.5	6.5	49	19	58	0.6	0.3	90	0.72	27.5	55	2.04	2600
ZKLF 3080.2RS	30	80	28	3	45.5	6.5	54	19	63	0.6	0.3	60	0.78	29	64	2.37	2200
ZKLF 3590.2RS	35	90	34	3	52	8.5	63	25	75	0.6	0.3	90	1.13	41	89	3.3	2000
ZKLF 40100.2RS	40	100	34	3	58	8.5	68	25	80	0.6	0.3	90	1.46	43	101	3.75	1800
ZKLF 50115.2RS	50	115	34	3	72	8.5	82	25	94	0.6	0.3	60	1.86	46.5	126	4.65	1500
ZKLF 1255.2Z	12	55	25	3	25	6.5	33.5	17	42	0.6	0.3	120	0.37	17	24.7	0.91	7600
ZKLF 1260.2Z	15	60	25	3	28	6.5	36	17	46	0.6	0.3	120	0.43	17.9	28	1.04	7000
ZKLF 1762.2Z	17	62	25	3	30	6.5	38	17	48	0.6	0.3	120	0.45	18.8	31	1.15	6600
ZKLF 2068.2Z	20	68	28	3	34.5	6.5	44	19	53	0.6	0.3	90	0.61	26	47	1.74	5400
ZKLF 2575.2Z	25	75	28	3	40.5	6.5	49	19	58	0.6	0.3	90	0.72	27.5	55	2.04	4700
ZKLF 3080.2Z	30	80	28	3	45.5	6.5	54	19	63	0.6	0.3	60	0.78	29	64	2.37	4300
ZKLF 3590.2Z	35	90	34	3	52	8.5	63	25	75	0.6	0.3	90	1.13	41	89	3.3	3800
ZKLF 40100.2Z	40	100	34	3	58	8.5	68	25	80	0.6	0.3	90	1.46	43	101	3.75	3300
ZKLF 50115.2Z	50	115	34	3	72	8.5	82	25	94	0.6	0.3	60	1.86	46.5	126	4.65	3000
ZKLF 1255.2RS PE	12	55	25	3	25	6.8	33.5	17	42	0.6	0.3	120	0.37	17	24.7	0.91	3800
ZKLF 1260.2RS PE	15	60	25	3	28	6.8	36	17	46	0.6	0.3	120	0.43	17.9	28	1.04	3500
ZKLF 1762.2RS PE	17	62	25	3	30	6.8	38	17	48	0.6	0.3	120	0.45	18.8	31	1.15	3300
ZKLF 2068.2RS PE	20	68	28	3	34.5	6.8	44	19	53	0.6	0.3	90	0.61	26	47	1.74	3000
ZKLF 2575.2RS PE	25	75	28	3	40.5	6.8	49	19	58	0.6	0.3	90	0.72	27.5	55	2.04	2600
ZKLF 3080.2RS PE	30	80	28	3	45.5	6.8	54	19	63	0.6	0.3	60	0.78	29	64	2.37	2200
ZKLF 3590.2RS PE	35	90	34	3	52	8.8	63	25	75	0.6	0.3	90	1.13	41	89	3.3	2000
ZKLF 40100.2RS PE	40	100	34	3	58	8.8	68	25	80	0.6	0.3	90	1.46	43	101	3.75	1800
ZKLF 50115.2RS PE	50	115	34	3	72	8.8	82	25	94	0.6	0.3	60	1.86	46.5	126	4.65	1500

(1) Weight≈(kg)

(2) Suffix PE: increased tolerances